

Stainless Steel NEMA 56C 12V&24V Washdown DC Motors
Dimension Chart (All Dimensions in Inch.)

Model No.	D	2E	F	2F1	H	O	U	V	AB	AH
MD01ILSS	3.5	4.88	3	—	0.34	5.63	0.625	1.88	4.13	2.06
MD01HLSS	3.5	4.88	3	—	0.34	5.63	0.625	1.88	4.13	2.06
MD01ILSS1	3.5	4.88	3	—	0.34	4.95	0.625	1.88	4.13	2.06
MD01HLSS1	3.5	4.88	3	—	0.34	4.95	0.625	1.88	4.13	2.06
MD02ILSS	3.5	4.88	3	—	0.34	5.63	0.625	1.88	4.13	2.06
MD02HLSS	3.5	4.88	3	—	0.34	5.63	0.625	1.88	4.13	2.06
MD02ILSS1	3.5	4.88	3	—	0.34	4.95	0.625	1.88	4.13	2.06
MD02HLSS1	3.5	4.88	3	—	0.34	4.95	0.625	1.88	4.13	2.06
MD03ILSS	3.5	4.88	3	—	0.34	5.63	0.625	1.88	4.13	2.06
MD03HLSS	3.5	4.88	3	—	0.34	5.63	0.625	1.88	4.13	2.06
MD03ILSS1	3.5	4.88	3	—	0.34	4.95	0.625	1.88	4.13	2.06
MD03HLSS1	3.5	4.88	3	—	0.34	4.95	0.625	1.88	4.13	2.06
MD04ILSS	3.5	4.88	3	—	0.34	5.63	0.625	1.88	4.13	2.06
MD04HLSS	3.5	4.88	3	—	0.34	5.63	0.625	1.88	4.13	2.06
MD04ILSS1	3.5	4.88	3	—	0.34	4.95	0.625	1.88	4.13	2.06
MD04HLSS1	3.5	4.88	3	—	0.34	4.95	0.625	1.88	4.13	2.06
MD05ILSS	3.5	4.88	3	—	0.34	5.63	0.625	1.88	4.13	2.06
MD05HLSS	3.5	4.88	3	—	0.34	5.63	0.625	1.88	4.13	2.06
MD05ILSS1	3.5	4.88	3	—	0.34	4.95	0.625	1.88	4.13	2.06
MD05HLSS1	3.5	2.44	3	—	0.34	4.95	0.625	1.88	4.13	2.06

AJ	AK	BA	BB	BD	TAP	C
5.875	4.5	2.75	0.12	6.5	3/8-16	11.6
5.875	4.5	2.75	0.12	6.5	3/8-16	11.6
5.875	4.5	2.75	0.12	6.5	3/8-16	11.6
5.875	4.5	2.75	0.12	6.5	3/8-16	11.6
5.875	4.5	2.75	0.12	6.5	3/8-16	11.6
5.875	4.5	2.75	0.12	6.5	3/8-16	11.6
5.875	4.5	2.75	0.12	6.5	3/8-16	11.6
5.875	4.5	2.75	0.12	6.5	3/8-16	11.6
5.875	4.5	2.75	0.12	6.5	3/8-16	12.4
5.875	4.5	2.75	0.12	6.5	3/8-16	12.4
5.875	4.5	2.75	0.12	6.5	3/8-16	12.4
5.875	4.5	2.75	0.12	6.5	3/8-16	12.4
5.875	4.5	2.75	0.12	6.5	3/8-16	14
5.875	4.5	2.75	0.12	6.5	3/8-16	14
5.875	4.5	2.75	0.12	6.5	3/8-16	14
5.875	4.5	2.75	0.12	6.5	3/8-16	14
5.875	4.5	2.75	0.12	6.5	3/8-16	14.8
5.875	4.5	2.75	0.12	6.5	3/8-16	14.8
5.875	4.5	2.75	0.12	6.5	3/8-16	14.8
5.875	4.5	2.75	0.12	6.5	3/8-16	14.8